

iNTO INTERIOR PAINT

UULA COLOR 2018

Type

Latex-free, fast drying, breathable and odourless water-borne paint for interior walls and roofs. iNTO is safe, eco-friendly and easy to use. The reason iNTO is ecological are the renewable natural oils that work as the binder.

Intended use

Unpainted or previously painted various interior wood and stone surfaces such as walls and roofs in dry places. Can be used on building paper and on brick surfaces.

Technical qualities

Density approx. 1.3 kg/L

Gloss grade: Semi- matt and matt.

Emission class M1 in building materials.

Does not contain any VOC.

Washability class SFS 3755: iNTO matt over 2000 brushes,

iNTO semi-matt over 5000 brushes.

Non-flammable.

Colours

White and tints made to A- and C-bases according to Uula colour charts.

Can also be tinted according to most common colour charts.

Application & conditions

Ordinary paint brush, paint roller or high-pressure paint sprayer.

The surface to be painted must be dry, the relative air humidity below 80 % and the temperature at least +10°C.

Drying time

Tack-free in approx. 30 minutes. Can be painted over after 2 hours.

(+20°C and relative air humidity below 80%)

Coverage

Approx 7 m²/L depending on the coarseness and porosity of the surface.

Thinner

Water

Cleaning of equipment

Clean the equipment with soap and water right after you have finished painting.

Container sizes

0.9 L, 2.7 L and 9 L.

Storage and disposal

Keep in a cool and dry place. DO NOT ALLOW TO FREEZE!

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point.



Painting instructions

Unpainted surface

Wash dirty surfaces with uula Washing Agent following the instructions. Allow to dry thoroughly before painting. Level all cracks and holes in the surface with putty if necessary. Apply two coats of iNTO Interior Paint. Thin with water if necessary.

Old painted surface

Remove peeling and flaking old paint. Sand a glossy or hard surface with a sandpaper. Wash dirty surfaces with Uula Paint Washing Agent following the instructions. Allow to dry thoroughly before painting. Level all cracks and holes in the surface with putty if necessary.

Apply one or two coats of iNTO Interior Paint. Thin with water if necessary.

Further treatment of the surface

Be really careful with all painted surfaces during the first month. Clean the surface only with soft rags and sponges that do not scratch the surface. Use only neutral washing agents. Rinse the surfaces carefully.

Points to note

- *Stir well before use and during painting
- *Reserve enough paint for a large surface in order to avoid potential colour variations in different batches.
- *Do a test painting to ensure that the colour is correct.
- *Always use enough paint.
- *Choose to colour in the same lighting and space where the painting will be done.
- *In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuoite Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.