

UULA BOILED LINSEED OIL (VARNISH)

UULA COLOR 2018

Type

Traditional high-quality linseed oil made of pressed linseed by boiling.

Intended use

Can be used as a binding agent for self-made paints, glazing, graining and marbling mixtures. Also for thinning of paints and for oil treatment of wood surfaces.

Technical qualities

Density approx. 0,9 kg/L

Container size

1 L, 3 L and 10 L.

Storage & disposal

Keep in a cool and dry place. Keep out of the reach of children. Does not freeze.

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point.

Fire classification

Non-flammable.

Caution: Linseed oil on cleaning rags etc. may catch fire by itself. Oily rags and cloths etc. should be burned or rinsed in water before putting into refuse bins.

UULA LINSEED OIL

UULA COLOR 2018

Type

Traditional high-quality linseed oil made of pressed linseed (approx. 60°C).

Intended use

For oiling interior wood surfaces. Uula Linseed Oil has traditionally been used also for oiling and impregnating wood boats.

Technical qualities

Density approx. 0.9 kg/L.

Container size

1 L, 3 L and 10 L.

Storage & disposal

Keep in a cool and dry place. Keep out of the reach of children. Does not freeze.

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point.

Fire classification

Non-flammable.

Caution: Linseed oil on cleaning rags etc. may catch fire by itself. Oily rags and cloths etc. should be burned or rinsed in water before putting into refuse bins.

In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.