

# iNTO INTERIOR PRIMER

UULA COLOR 2018

## **Type**

Latex-free and odourless water-borne furniture paint. INTO is safe, eco-friendly and easy to use. Improves adhesion. The reason INTO is ecological are the renewable natural oils that work as the binder.

## **Intended use**

Unpainted or previously painted various wood and stone for interior surfaces such as. Roofs and walls, furniture, doors and frames. Over-paintable with INTO interior paint, Into furniture paint, window and Door paint and Eggshell Interior Oil Paint. Do not use on floors. Can also be used as matt interior paint.

## **Technical qualities**

Density approx. 1.3 kg/L.  
Gloss grade: Matt.  
Emission class M1 in building materials.  
Does not contain any VOC.  
Non-flammable.

## **Colours**

White and tints made to according to Uula colour charts.  
Can also be tinted according to most common colour charts.

## **Application & conditions**

Ordinary paint brush, paint roller or high-pressure paint sprayer.  
The surface to be painted must be dry, the relative air humidity below 80 % and the temperature at least +10°C.

## **Drying time**

Tack-free in approx. 30 minutes. Can be painted over and grinded after 4 h. (+20°C and relative air humidity below 80%)

## **Coverage**

Approx 7 m<sup>2</sup>/L depending on the coarseness and porosity of the surface.

## **Thinner**

Water

## **Cleaning of equipment**

Clean the equipment with soap and water right after you have finished painting.

## **Container sizes**

0.9 L, 2.7 L and 9 L.

## **Storage and disposal**

Keep in a cool and dry place. DO NOT ALLOW TO FREEZE!  
Dry and empty containers can be taken to a refuse dump.  
Liquid waste must be taken to a municipal hazardous waste collection point.



## **Painting instructions:**

### **Preparations**

Wash dirty surfaces with Uula Paint Washing Agent following the instructions. Allow to dry thoroughly before painting.

### **Priming**

Prime new wooden surfaces with INTO interior Primer. If the surface is very porous the paint can be thinned approx. 15% with water. Level all cracks and holes in the surface with putty if necessary. Sand filled putty spots and paint with INTO Interior Primer.

### **Finishing**

According to the chosen paint type

### **Points to note**

\*Stir well before use and during painting

\*Surfaces painted with INTO interior paint can be levelled with any putties and spackles for intended use.

\*In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.