

## **Type**

The high-quality Wood Tar is made by heating (dry distilling) pine. The process also generates pitch, which is essential in protecting a surface. Turpentine or other solvents have not been added to the Tar.

## **Intended use**

Tar is used to protect exterior wooden surfaces, e.g. shingle and board roofs, sledges, boats, tools etc.

## **Colours**

Brown (varies).

## **Technical qualities**

Density approx. 1.0 kg/L.

## **Drying time**

Absorption time basically equals the final drying time.

## **Coverage**

3–5 m<sup>2</sup>/L, depending on the surface.

## **Thinner**

Uula Universal Thinner or wood turpentine, which is recommended for enhancing absorption and decreasing stickiness.

## **Cleaning of equipment**

Turpentine

## **Container sizes**

1 L, 3 L and 10 L.

## **Storage & disposal**

Keep out of the reach of children. Does not freeze.

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point.

## **Fire classification**

Non-flammable.

In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.