

## **Type**

Traditional translucent wood preservative for exterior use. Contains tar and boiled linseed oil. Uula Roslag mahogany leaves the grains of the wood visible and gives a surface that protects from the weather conditions and sunlight.

## **Intended use**

Old and new untreated wood surfaces and old exterior wood surfaces impregnated with agents that do not form a hard coating (also old pressure impregnated surfaces), e.g. log or board walls, wood boats and jetties.

## **Technical qualities**

Density approx. 0.95kg/L.

Gloss grade: Semi-matt.

VOC emissions: under 350g/l

EU VOC -limit value: (cat A/f) 700g/L (2010).

## **Colours**

Uula Colour Chart translucent colours.

Uula Roslag Mahogany is tinted with colour pastes made from genuine colour pigments. The colour and texture (planed or sawn timber etc.) of the surface to be treated must be taken into consideration when choosing a translucent paint shade. A small test is recommended before the actual treatment. The surface attains its final colour when the tar has been absorbed completely.

## **Application & conditions**

Apply by ordinary paint brush or levelling paint brush.

The surface to be painted must be dry and the moisture content of the wood below 15 %. The relative air humidity must be below 80 % and the temperature at least +5°C.

## **Drying time**

In sunlight the surface can dry even in 24 hours. On shadowy surfaces drying time up to 3–4 weeks. (To be considered particularly in garden furniture, jetties etc). Withstands normal rain a couple of hours after painting.

Dense and new planed surface increase drying and absorption time significantly.

## **Coverage**

Planed timber 8–10 m<sup>2</sup>/L, rough sawn timber 6–8 m<sup>2</sup>/L.

## **Thinner**

The product does not need to be thinned

## **Container sizes**

0.9 L, 2.7 L, 9 L

## **Cleaning of equipment**

Clean the equipment with Uula Universal Thinner or petroleum spirit and rinse with soap and water.

### **Storage & disposal**

Keep in a cool and dry place. Keep out of the reach of children. Does not freeze. Always stir well before use as the pigments settle during storage. Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point.

### **Fire classification**

Non-flammable.

Caution: Linseed oil on cleaning rags etc. may catch fire by itself. Oily rags and cloths etc. should be burned or rinsed in water before putting into refuse bins.

### **Painting Instructions:**

#### **Preparation**

Wash dirty surfaces with Uula Paint Washing Agent and mouldy ones with Uula Mould Cleaning Agent. Remove peeling and flaking old wood preservative with wire brush and scraper.

#### **Finishing**

Roslag Mahogany is to be applied twice. The second treatment either immediately before the previous coat has dried or after 1–2 years.

**A new, planed surface must be roughened before surface treatment or allowed to age for 1 year.**

### **Points to note**

\*Reserve enough paint for a large surface in order to avoid potential colour variations in different batches. Due to colour differences in Tar the colour might have small variations in colour in different batches.

\*The paint must always be stirred well before and during use.

\*Paint also the cross-sectional surfaces of the timber carefully.

\*Maintenance painting should be done with the original or darker shade.

\*Do not paint in rain, direct sunlight or on sun heated surfaces.

\*In maintenance painting tinting base (RM 222) can be mixed with tinted Roslag mahogany by 1:1 to reduce the opacity of the colour.

\*If there is mould and dirt in the surface, the surface should be washed.

\*More detailed instructions for maintenance and cleaning can be found in our website [www.uula.fi](http://www.uula.fi)

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.