

Type

Ready-to-use biocide based cleaning and disinfection solution for exterior use. Is suitable for painted or un-painted wood, stone and plaster surfaces. Works also as a preventive primer to slow down the possible formation of mold and algae growth.

Intended use

For the protection of any exterior wood surfaces against mould, decay and blue stain prior to painting or other surface treatment.

Technical qualities

Density approx. 1,0 kg/L.

Contains: VOC max. 30 g/L.

EU VOC -limit value: (cat A/h) 30g/L (2010).

Application & conditions

Brushing, spraying or immersion.

The surface to be treated can be moist or dry.

Do not apply when it's raining.

Drying time

At 20°C and 80 % relative humidity: Approx. 1 hour.

The surface can be painted after 24 hours.

Coverage

Rough surfaces 4–5 m²/L, planed surfaces 7–8 m²/L.

Spraying or immersion uses more of the agent.

Thinner

The product is ready to use as it is, do not thin.

Cleaning of equipment

Clean the equipment with soap and water right after you have finished painting.

Container sizes

1 L, 5 L and 10 L

Storage and disposal

Keep in a cool and dry place. Do not allow to freeze!

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point.

Fire classification

Non-flammable.

Treatment instructions

Protection during construction

All types of wood can be treated with Uula Anti-Mould Agent by brushing or spraying. For example, it is advisable to protect a log-building immediately after construction.

Treating an old surface

Clean any dust from the surface. Wash dirty surfaces with Uula Washing Agent. Moulded surface must be washed with Uula Mould Cleaning Agent. Anti-mould Agent is applied by brushing or spraying onto the surface.

Painting after treatment

The surface can be treated with any type of paint and wood protection agent.

Points to note

*If the surface is primed with Uula Exterior Primer, Anti Mould Agent treatment is not required.

*We recommend that the Anti Mould Agent is treated with one coat only. Extra coats do not improve the efficiency of the product.

*In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuoite Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.