

Type

Fast-drying, odourless and water-soluble special oil for wooden surfaces in exteriors. Gives a surface that protects from moisture and dirt and reduces cracking of the wood.

Intended use

New and old untreated wooden surfaces e.g. patios, piers, timber and board walls, garden furniture, wooden stairs, window panels and wooden boats. Pressure impregnated surfaces and old exterior wooden surfaces that have been treated with agents that do not form a hard coat.

Technical qualities

Density 0.9 kg/L.

Does not contain VOC.

Non-flammable

Colours

Colourless, can be tinted according to the translucent colours in Uula interior and traditional colour charts. Can also be tinted according to most common colour charts. (translucent colours)

Application & conditions

Paint brush or levelling paint brush.

The surface to be painted must be dry, the humidity of the wood below 15 %, the relative air humidity below 80 % and the temperature at least +10°C.

Drying time

At 20°C and <80 % relative humidity: Tack-free in 1 hour.

A new coat of paint can be applied after 4 hours.

Coverage

Sawn surface approx. 6 m²/L, planed surface approx. 10 m²/L.

Cleaning of equipment

Clean the equipment with soap and water right after you have finished painting.

Container sizes

0.9 L, 2.7 L, 9 L.

Storage & disposal

Keep in a cool and dry place. Do not allow to freeze!

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point.

Painting instructions

Preparation

Brush off dust. Wash dirty surfaces with Uula Mould Cleaning Agent. Remove peeling and loose old wood preservative with a wire brush and scraper. Remember to sand new planed surfaces rough to ensure adhesion.

Finishing

Apply 2 coats of Uula Decking Oil. Let the surface dry in between treatments.

Points to note and painting tips

- *Always stir well before and during use.
- *Reserve enough paint for a large surface to avoid potential colour variations in different batches.
- *The colour and texture (planed or sawn timber etc.) of the surface to be treated must be taken into consideration when choosing a translucent paint shade.
- *A small test is recommended before the actual treatment.
- *Paint also cross-sectional surfaces carefully.
- *It is recommended to roughen a new planed surface or to let the surface age 1-2 years before surface treatment for better absorption. Drying takes longer on new planed surface.
- *Do not paint in rain, direct sunlight or on sun heated surfaces.
- *If the surface becomes dirty or mouldy, it should be cleaned or washed.
- *More detailed instructions for maintenance and cleaning can be found in our website www.uula.fi
- *In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.