



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation


Uula Linseed Oil Paint C-Base



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Uula Linseed Oil Paint
C-Base
- Other means of identification:**
- UFI:** KTD1-K0H9-C00S-65XS
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Painting work.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Uula Color Oy
Yttiläntie 265
FI-32920 Kauvatsa - Finland
Phone: +358 10 820 0020
uula@uula.fi
<http://www.uula.fi>
- 1.4 Emergency telephone number:** Emergency telephone number Europe: 112

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
- CLP Regulation (EC) No 1272/2008:**
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411
Eye Irrit. 2: Eye irritation, Category 2, H319
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
- 2.2 Label elements:**
- CLP Regulation (EC) No 1272/2008:**
- Warning**
- 
- Hazard statements:**
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
- Precautionary statements:**
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P264: Wash contaminated skin thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501: Dispose of contents/container according to the separated collection system used in your municipality.
- Supplementary information:**
Contains 2-octyl-2H-isothiazol-3-one, Cobalt bis(2-ethylhexanoate).
- Substances that contribute to the classification**
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; 4,5-dichloro-2-octyl-2H-isothiazol-3-one
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**Uula Linseed Oil Paint
C-Base****SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.1 Substance:**

Non-applicable

3.2 Mixture:**Chemical description:** Dispersion of pigments in solvents**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 68649-95-6 EC: 272-038-8 Index: Non-applicable REACH: 01-2119484875-20-XXXX	Linseed oil, oxidized⁽¹⁾ Not classified Regulation 1272/2008	30 - <40 %
CAS: Non-applicable EC: 918-481-9 Index: Non-applicable REACH: 01-2119457273-39-XXXX	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics⁽²⁾ Self-classified Regulation 1272/2008 Asp. Tox. 1: H304; EUH066 - Danger	10 - <15 %
CAS: 1065336-91-5 EC: 915-687-0 Index: Non-applicable REACH: 01-2119491304-40-XXXX	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate⁽²⁾ Self-classified Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Repr. 2: H361f; Skin Sens. 1A: H317 - Warning	<0,5 %
CAS: 61789-72-8 EC: 939-290-7 Index: Non-applicable REACH: 01-2119970169-28-XXXX	Quaternary ammonium compounds, benzyl-C16-18-alkyldimethyl, chlorides⁽²⁾ Self-classified Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1B: H314 - Danger	<0,4 %
CAS: 64359-81-5 EC: 264-843-8 Index: 613-335-00-8 REACH: Non-applicable	4,5-dichloro-2-octyl-2H-isothiazol-3-one⁽²⁾ Self-classified Regulation 1272/2008 Acute Tox. 2: H330; Acute Tox. 4: H302+H312; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Corr. 1B: H314; Skin Sens. 1A: H317; STOT SE 3: H335; EUH071 - Danger	<0,2 %
CAS: 872-50-4 EC: 212-828-1 Index: 606-021-00-7 REACH: 01-2119472430-46-XXXX	N-methyl-2-pyrrolidone⁽²⁾ ATP ATP09 Regulation 1272/2008 Eye Irrit. 2: H319; Repr. 1B: H360D; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger	<0,15 %
CAS: 26530-20-1 EC: 247-761-7 Index: 613-112-00-5 REACH: 01-2120768921-45-XXXX	2-octyl-2H-isothiazol-3-one⁽²⁾ Self-classified Regulation 1272/2008 Acute Tox. 3: H311+H331; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	<0,15 %
CAS: 55406-53-6 EC: 259-627-5 Index: 616-212-00-7 REACH: 01-2120762115-60-XXXX	3-iodo-2-propynyl Butylcarbamate⁽²⁾ ATP ATP06 Regulation 1272/2008 Acute Tox. 3: H331; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Sens. 1: H317; STOT RE 1: H372 - Danger	<0,07 %
CAS: 136-52-7 EC: 205-250-6 Index: Non-applicable REACH: 01-2119524678-29-XXXX	Cobalt bis(2-ethylhexanoate)⁽²⁾ Self-classified Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 1B: H360; Skin Sens. 1A: H317 - Danger	<0,03 %

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
	Acute	Chronic
4,5-dichloro-2-octyl-2H-isothiazol-3-one CAS: 64359-81-5 EC: 264-843-8	100	100
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5	10	1

Identification	Specific concentration limit
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	% (w/w) >=10: STOT SE 3 - H335

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Linseed Oil Paint C-Base

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Specific concentration limit
2-octyl-2H-isothiazol-3-one CAS: 26530-20-1 EC: 247-761-7	% (w/w) >=0,05; Skin Sens. 1 - H317

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Uula Linseed Oil Paint C-Base



SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



**Uula Linseed Oil Paint
C-Base**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	IOELV (8h)	10 ppm
	IOELV (STEL)	20 ppm	80 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Linseed oil, oxidized CAS: 68649-95-6 EC: 272-038-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	69,4 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	49 mg/m ³	Non-applicable
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,68 mg/m ³	Non-applicable
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	4,8 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,4 mg/m ³	40 mg/m ³
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
	Inhalation	0,07 mg/m ³	1,16 mg/m ³	0,023 mg/m ³	1,16 mg/m ³
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,2351 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Linseed oil, oxidized CAS: 68649-95-6 EC: 272-038-8	Oral	Non-applicable	Non-applicable	8,33 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	41,7 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,5 mg/m ³	Non-applicable
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	Oral	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,17 mg/m ³	Non-applicable
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	Oral	Non-applicable	Non-applicable	0,85 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,4 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	3,6 mg/m ³	4,5 mg/m ³
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	Oral	Non-applicable	Non-applicable	0,175 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,037 mg/m ³

PNEC:

Identification		Fresh water		Marine water	
		STP	Intermittent	STP	Intermittent
Linseed oil, oxidized CAS: 68649-95-6 EC: 272-038-8	Soil	1,55 mg/L	21,7 mg/kg	0,01 mg/L	0,001 mg/L
	Soil	0,1 mg/L	0,1 mg/L	Non-applicable	Non-applicable
	Oral	0,0667 g/kg	0,0667 g/kg	Non-applicable	Non-applicable
	Oral	0,0667 g/kg	0,0667 g/kg	Non-applicable	Non-applicable
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	Soil	1 mg/L	0,21 mg/kg	0,002 mg/L	0 mg/L
	Soil	1 mg/L	0,21 mg/kg	0,002 mg/L	0 mg/L
	Intermittent	0,009 mg/L	0,009 mg/L	1,05 mg/kg	1,05 mg/kg
	Oral	Non-applicable	Non-applicable	Non-applicable	0,11 mg/kg

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



**Uula Linseed Oil Paint
C-Base**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Quaternary ammonium compounds, benzyl-C16-18-alkyldimethyl, chlorides CAS: 61789-72-8 EC: 939-290-7	STP	0,8 mg/L	Fresh water	0,00042 mg/L
	Soil	1,66 mg/kg	Marine water	0,000096 mg/L
	Intermittent	0,0005 mg/L	Sediment (Fresh water)	68 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	15,75 mg/kg
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	STP	10 mg/L	Fresh water	0,25 mg/L
	Soil	0,07 mg/kg	Marine water	0,025 mg/L
	Intermittent	5 mg/L	Sediment (Fresh water)	1,09 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,109 mg/kg
2-octyl-2H-isothiazol-3-one CAS: 26530-20-1 EC: 247-761-7	STP	Non-applicable	Fresh water	0,0022 mg/L
	Soil	0,0082 mg/kg	Marine water	0,00022 mg/L
	Intermittent	0,00122 mg/L	Sediment (Fresh water)	0,0475 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00475 mg/kg
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5	STP	0,44 mg/L	Fresh water	0,001 mg/L
	Soil	0,005 mg/kg	Marine water	0 mg/L
	Intermittent	0,001 mg/L	Sediment (Fresh water)	0,017 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,002 mg/kg
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	STP	0,37 mg/L	Fresh water	0,00062 mg/L
	Soil	10,9 mg/kg	Marine water	0,00236 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	53,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	69,8 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.

- CONTINUED ON NEXT PAGE -



Safety data sheet



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Uula Linseed Oil Paint C-Base



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	10,5 % weight
V.O.C. density at 20 °C:	130,99 kg/m ³ (130,99 g/L)
Average carbon number:	11,91
Average molecular weight:	129,59 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	According to the markings on the package
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	Non-applicable *
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	1247,2 kg/m ³
Relative density at 20 °C:	1,247
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm ² /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Insoluble in water
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Linseed Oil Paint C-Base

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flash Point:	67 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	265 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Linseed Oil Paint C-Base

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Talc (3); Polyurethane foams (3); Cobalt bis(2-ethylhexanoate) (2B); Fatty acids, tall-oil, cobalt salts (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Linseed oil, oxidized CAS: 68649-95-6 EC: 272-038-8	>2000 mg/kg	>2000 mg/kg	
	>2000 mg/kg	>2000 mg/kg	
	>20 mg/L	>20 mg/L	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 918-481-9	>2000 mg/kg	>2000 mg/kg	
	>2000 mg/kg	>2000 mg/kg	
	>20 mg/L	>20 mg/L	
2-octyl-2H-isothiazol-3-one CAS: 26530-20-1 EC: 247-761-7	125 mg/kg	311 mg/kg	Rat
	311 mg/kg	311 mg/kg	
	3 mg/L (ATEi)	3 mg/L (ATEi)	

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Uula Linseed Oil Paint
C-Base

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	Route	Toxicity	
4,5-dichloro-2-octyl-2H-isothiazol-3-one CAS: 64359-81-5 EC: 264-843-8	LD50 oral	567 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	0,5 mg/L (ATEi)	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	LD50 oral	3230 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
Quaternary ammonium compounds, benzyl-C16-18-alkyldimethyl, chlorides CAS: 61789-72-8 EC: 939-290-7	LD50 oral	344 mg/kg	Rat
	LD50 dermal	2730 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L	
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rat
	LC50 inhalation	>20 mg/L	
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5	LD50 oral	1100 mg/kg	Rat
	LD50 dermal	2100 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L	
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	

Acute Toxicity Estimate (ATE mix):

ATE mix	Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method) Non-applicable
Dermal	251008,88 mg/kg (Calculation method) 0 %
Inhalation	252,47 mg/L (4 h) (Calculation method) 0 %

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
	Route	Toxicity		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	LC50	0,9 mg/L (96 h)	Danio rerio	Fish
	EC50	Non-applicable		
	EC50	1,7 mg/L (72 h)	Desmodesmus subspicatus	Algae
Quaternary ammonium compounds, benzyl-C16-18-alkyldimethyl, chlorides CAS: 61789-72-8 EC: 939-290-7	LC50	0,1 mg/L (96 h)	Danio rerio	Fish
	EC50	0,059 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0,102 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
4,5-dichloro-2-octyl-2H-isothiazol-3-one CAS: 64359-81-5 EC: 264-843-8	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	LC50	832 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	4897 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	500 mg/L (72 h)	Scenedesmus subspicatus	Algae

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**Uula Linseed Oil Paint
C-Base****SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Concentration		Species	Genus
2-octyl-2H-isothiazol-3-one CAS: 26530-20-1 EC: 247-761-7	LC50	2,6 mg/L (96 h)	N/A	Fish
	EC50	0,5 mg/L (48 h)	N/A	Crustacean
	EC50	0,2 mg/L (96 h)	N/A	Algae
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5	LC50	0,07 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0,09 mg/L (96 h)	Mysidopsis bahia	Crustacean
	EC50	0,05 mg/L (72 h)	Scenedesmus subspicatus	Algae
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	NOEC	Non-applicable		
	NOEC	1 mg/L	Daphnia magna	Crustacean
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	NOEC	Non-applicable		
	NOEC	12,5 mg/L	Daphnia magna	Crustacean
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5	NOEC	0,0084 mg/L	Pimephales promelas	Fish
	NOEC	0,0499 mg/L	Daphnia magna	Crustacean
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	NOEC	0,21 mg/L	Pimephales promelas	Fish
	NOEC	0,1697 mg/L	Aelosoma sp.	Crustacean

12.2 Persistence and degradability:**Substance-specific information:**

Identification	Degradability		Biodegradability	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	BOD5	Non-applicable	Concentration	20 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	38 %
Quaternary ammonium compounds, benzyl-C16-18-alkyldimethyl, chlorides CAS: 61789-72-8 EC: 939-290-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	65 %
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	BOD5	1,09 g O2/g	Concentration	100 mg/L
	COD	1,6 g O2/g	Period	28 days
	BOD5/COD	0,68	% Biodegradable	73 %

12.3 Bioaccumulative potential:**Substance-specific information:**

Identification	Bioaccumulation potential	
Quaternary ammonium compounds, benzyl-C16-18-alkyldimethyl, chlorides CAS: 61789-72-8 EC: 939-290-7	BCF	79
	Pow Log	
	Potential	Moderate
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	BCF	0.23
	Pow Log	-0.46
	Potential	Low
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5	BCF	36
	Pow Log	2.4
	Potential	Moderate

12.4 Mobility in soil:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Linseed Oil Paint C-Base

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	Koc	204400	Henry	0E+0 Pa·m ³ /mol
	Conclusion	Immobile	Dry soil	No
	Surface tension	Non-applicable	Moist soil	No
Quaternary ammonium compounds, benzyl-C16-18-alkyldimethyl, chlorides CAS: 61789-72-8 EC: 939-290-7	Koc	1640329	Henry	Non-applicable
	Conclusion	Immobile	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	4,007E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**Uula Linseed Oil Paint
C-Base****SECTION 14: TRANSPORT INFORMATION (continued)**

- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate)
- 14.3 Transport hazard class(es):** 9
Labels: 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
Special regulations: 274, 335, 375, 601
Tunnel restriction code: -
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate)
- 14.3 Transport hazard class(es):** 9
Labels: 9
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**
Special regulations: 335, 969, 274
EmS Codes: F-A, S-F
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate)
- 14.3 Transport hazard class(es):** 9
Labels: 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Uula Linseed Oil Paint C-Base



SECTION 15: REGULATORY INFORMATION (continued)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one, 3-iodo-2-propynyl Butylcarbamate, 2-octyl-2H-isothiazol-3-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): N-methyl-2-pyrrolidone

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 4,5-dichloro-2-octyl-2H-isothiazol-3-one (Product-type 7, 8, 9, 10, 11, 21) ; 2-octyl-2H-isothiazol-3-one (Product-type 6, 7, 8, 9, 10, 11, 13) ; 3-iodo-2-propynyl Butylcarbamate (Product-type 6, 7, 8, 9, 10, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains N-methyl-2-pyrrolidone. 1. | Shall not be placed on the market as a substance on its own or in mixtures in a concentration equal to or greater than 0,3 % after 9 May 2020 unless manufacturers, importers and downstream users have included in the relevant chemical safety reports and safety data sheets, Derived No-Effect Levels (DNELs) relating to exposure of workers of 14,4 mg/m³ for exposure by inhalation and 4,8 mg/kg/day for dermal exposure. | 2. | Shall not be manufactured, or used, as a substance on its own or in mixtures in a concentration equal to or greater than 0,3 % after 9 May 2020 unless manufacturers and downstream users take the appropriate risk management measures and provide the appropriate operational conditions to ensure that exposure of workers is below the DNELs specified in paragraph 1. | 3. | By way of derogation from paragraphs 1 and 2, the obligations laid down therein shall apply from 9 May 2024 in relation to placing on the market for use, or use, as a solvent or reactant in the process of coating wires.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

- H317: May cause an allergic skin reaction.
- H411: Toxic to aquatic life with long lasting effects.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Linseed Oil Paint C-Base

SECTION 16: OTHER INFORMATION (continued)

CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H330 - Fatal if inhaled.
Acute Tox. 3: H311+H331 - Toxic in contact with skin or if inhaled.
Acute Tox. 3: H331 - Toxic if inhaled.
Acute Tox. 4: H302 - Harmful if swallowed.
Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Repr. 1B: H360 - May damage fertility or the unborn child.
Repr. 1B: H360D - May damage the unborn child.
Repr. 2: H361f - Suspected of damaging fertility.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Skin Sens. 1A: Calculation method
Aquatic Chronic 2: Calculation method
Skin Irrit. 2: Calculation method
Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -