




Uula Oil Paint Thinner

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Uula Oil Paint Thinner
Other means of identification:
UFI: 7DE4-80V0-7006-7943
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Thinner for the application of paints and varnishes
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Uula Color Oy
Yttiläntie 265
FI-32920 Kauvatsa - Finland
Phone: +358 10 820 0020
uula@uula.fi
<http://www.uula.fi>
- 1.4 Emergency telephone number:** Emergency telephone number Europe: 112

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Asp. Tox. 1: Aspiration hazard, Category 1, H304
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger

Hazard statements:
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Precautionary statements:
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331: Do NOT induce vomiting.
P405: Store locked up.
P501: Dispose of contents/container according to the separated collection system used in your municipality.
Supplementary information:
EUH066: Repeated exposure may cause skin dryness or cracking.
Substances that contribute to the classification
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**
Non-applicable
- 3.2 Mixture:**

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Oil Paint Thinner

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Chemical description: Solvent/s

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | Concentration |
|---|---|----------------------|
| CAS: Non-applicable EC: 918-481-9 Index: Non-applicable REACH: 01-2119457273-39-XXXX | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics⁽¹⁾ Self-classified Regulation 1272/2008 Asp. Tox. 1: H304; EUH066 - Danger | 60 - <65 % |
| CAS: 68649-95-6 EC: 272-038-8 Index: Non-applicable REACH: 01-2119484875-20-XXXX | Linseed oil, oxidized⁽²⁾ Not classified Regulation 1272/2008 | 35 - <40 % |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Oil Paint Thinner

SECTION 5: FIREFIGHTING MEASURES (continued)

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Oil Paint Thinner

SECTION 7: HANDLING AND STORAGE (continued)

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|---|------------|----------------|----------------|----------------------|----------------|
| | | Systemic | Local | Systemic | Local |
| Linseed oil, oxidized CAS: 68649-95-6 EC: 272-038-8 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 69,4 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 49 mg/m ³ | Non-applicable |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|---|------------|----------------|----------------|------------------------|----------------|
| | | Systemic | Local | Systemic | Local |
| Linseed oil, oxidized CAS: 68649-95-6 EC: 272-038-8 | Oral | Non-applicable | Non-applicable | 8,33 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 41,7 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 14,5 mg/m ³ | Non-applicable |

PNEC:

| Identification | | | | | |
|---|--------------|-------------|-------------------------|----------------|--|
| Linseed oil, oxidized CAS: 68649-95-6 EC: 272-038-8 | STP | 1,55 mg/L | Fresh water | 0,01 mg/L | |
| | Soil | 21,7 mg/kg | Marine water | 0,001 mg/L | |
| | Intermittent | 0,1 mg/L | Sediment (Fresh water) | Non-applicable | |
| | Oral | 0,0667 g/kg | Sediment (Marine water) | Non-applicable | |

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---------------------------------------|---|--------------|--|
|  Mandatory hand protection | Protective gloves against minor risks |  | | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018 |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

- CONTINUED ON NEXT PAGE -





Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation




Uula Oil Paint Thinner



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|---|---------------------------------|---|
|  Mandatory face protection | Panoramic glasses against splash/projections. |  | EN 166:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|---------------|---|--------------|---|
| | Work clothing |  | | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|-------------------------------------|
| V.O.C. (Supply): | 61 % weight |
| V.O.C. density at 20 °C: | 499,5 kg/m ³ (499,5 g/L) |
| Average carbon number: | 12 |
| Average molecular weight: | 130 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

| | |
|--------------------------|------------------|
| Physical state at 20 °C: | Liquid |
| Appearance: | Oily |
| Colour: | Yellowish |
| Odour: | Solvent |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|------------------|
| Boiling point at atmospheric pressure: | 205 °C |
| Vapour pressure at 20 °C: | Non-applicable * |
| Vapour pressure at 50 °C: | Non-applicable * |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|-----------------------------|-------------------------|
| Density at 20 °C: | 818,8 kg/m ³ |
| Relative density at 20 °C: | 0,819 |
| Dynamic viscosity at 20 °C: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Oil Paint Thinner

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | |
|--|--------------------------|
| Kinematic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 40 °C: | <20,5 mm ² /s |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Non-applicable * |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |

Flammability:

| | |
|----------------------------|------------------|
| Flash Point: | 65 °C |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 265 °C |
| Lower flammability limit: | Non-applicable * |
| Upper flammability limit: | Non-applicable * |

Particle characteristics:

| | |
|-----------------------------|----------------|
| Median equivalent diameter: | Non-applicable |
|-----------------------------|----------------|

9.2 Other information:

Information with regard to physical hazard classes:

| | |
|--|------------------|
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |
| Corrosive to metals: | Non-applicable * |
| Heat of combustion: | Non-applicable * |
| Aerosols-total percentage (by mass) of flammable components: | Non-applicable * |

Other safety characteristics:

| | |
|---------------------------|------------------|
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|----------------|----------------|
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Not applicable | Not applicable | Avoid alkalis or strong bases |

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Oil Paint Thinner

SECTION 10: STABILITY AND REACTIVITY (continued)

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

Other information:

Non-applicable

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Oil Paint Thinner

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|--|----------------|-------------|-------|
| | LD50 oral | LD50 dermal | |
| Linseed oil, oxidized CAS: 68649-95-6 EC: 272-038-8 | >2000 mg/kg | >2000 mg/kg | |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 918-481-9 | >2000 mg/kg | >2000 mg/kg | |

Acute Toxicity Estimate (ATE mix):

| ATE mix | | Ingredient(s) of unknown toxicity |
|------------|-------------------------------------|-----------------------------------|
| Oral | >2000 mg/kg (Calculation method) | Non-applicable |
| Dermal | >2000 mg/kg (Calculation method) | Non-applicable |
| Inhalation | >20 mg/L (4 h) (Calculation method) | Non-applicable |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Not available

12.2 Persistence and degradability:

Not available

12.3 Bioaccumulative potential:

Not available

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Oil Paint Thinner

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ...):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H304: May be fatal if swallowed and enters airways.

Texts of the legislative phrases mentioned in section 3:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



Uula Oil Paint Thinner

SECTION 16: OTHER INFORMATION (continued)

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Classification procedure:

Asp. Tox. 1: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -